

Diverted (Table 19)													
WY	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Year
1999	137	129	139	139	135	130	97	130	135	156	140	134	1,601
2000	141	136	126	137	183	123	142	148	142	141	124	126	1,669
2001	140	134	126	128	125	123	143	135	126	129	127	120	1,557
2002	119	116	136	177	131	146	137	137	131	132	129	124	1,614
2003	128	123	98	141	59	202	137	137	116	134	128	120	1,521
2004	120	124	154	120	136	146	128	132	123	128	127	117	1,555
2005	138	99	119	106	122	51	141	151	99	164	125	119	1,434
Gaged Flow* (Table 15)													
1999	-	-	-	-	204	235	222	213	142	148	147	141	-
2000	143	138	133	149	193	213	151	-	-	-	-	-	-
2001	-	-	-	-	-	-	-	-	-	-	-	-	-
2002	-	-	127	171	128	143	132	134	129	130	125	117	-
2003	-	101	-	-	-	-	-	-	-	-	-	-	-
2004	-	-	-	-	-	-	130	131	126	129	128	122	-
2005	132	107	149	197	145	227	149	150	132	129	124	118	1,760
Gaged minus Diverted													
1999	-	-	-	-	69	105	126	83	6	-8	7	7	-
2000	2	2	7	11	10	90	9	-	-	-	-	-	-
2001	-	-	-	-	-	-	-	-	-	-	-	-	-
2002	-	-	-9	-6	-2	-3	-5	-3	-2	-2	-4	-7	-
2003	-	-22	-	-	-	-	-	-	-	-	-	-	-
2004	-	-	-	-	-	-	3	-1	4	1	1	5	-
2005	-6	7	30	91	23	176	8	-1	33	-35	-1	-1	326
% Diverted**													
1999	-	-	-	-	66%	55%	43%	61%	95%	105%	96%	95%	-
2000	99%	99%	95%	92%	95%	58%	94%	-	-	-	-	-	-
2001	-	-	-	-	-	-	-	-	-	-	-	-	-
2002	-	-	107%	104%	102%	102%	104%	102%	101%	102%	103%	106%	-
2003	-	121%	-	-	-	-	-	-	-	-	-	-	-
2004	-	-	-	-	-	-	98%	101%	97%	99%	99%	96%	-
2005	104%	93%	80%	54%	84%	22%	94%	101%	75%	127%	101%	101%	81%

* Gage sometimes does not measure total flow accurately due to bypassed flushing flows, flows that exceed pipeline intake capacity, and an increase in pipeline capacity during "blow offs."

** Diversions >100% of gaged flows due either to incomplete gaging of total flow and/or other discrepancies between metered diversions and gaged flows.

Liddell Spring Diversions versus Gaged Flows,
WYs 1999-2005 (ac-ft)

Table 20

Nolan Associates